

Blast Hose SM-1



This high quality brand belongs to the product group "pressure blast systems". Only the perfect configuration and match of all system components in a blast machine enable maximum blasting efficiency. Therefore Clemco offers an extensive and complete range of quality products.



Blast Hose SM-1

A modern blasting hose requires high demands on raw materials and the corresponding combination in different layers. Blast hoses also have to meet the highest safety standards and maximum economy. The Clemco blast hose convinces with its extreme abrasion resistance and sets standards in the industry. Its unique core quality allows the conveying of every common abrasive media, even particularly aggressive ones such as corundum. In addition, its antistatic hose construction provides the necessary protection against electrostatic charging. The SM-1 blasting hose with 36mm³ offers the highest abrasion resistance and thus impresses with a very long service life.

Length	20/40m mm
Blasting pressure	0 < > 12 bar
Operating temperature	-35°C < > +80°C
Standards	DIN ISO 4649: 2021 (36mm ³) EN ISO 3861:2021

blast hose SM-1 with high abrasion-resistant antistatic core (50 mm³)

item #	description	size
99850D	BLAST HOSE 19 X 7, SM-1	ID 19 mm - OD 33 mm (20 m oder 40 m roll)
99849D	BLAST HOSE 25 X 7, SM-1	ID 25 mm - OD 39 mm (20 m oder 40 m roll)
04256D	BLAST HOSE 32 X 8, SM-1	ID 32 mm - OD 48 mm (20 m oder 40 m roll)
99853D	BLAST HOSE 38 X 9, SM-1	ID 38 mm - OD 56 mm (40 m roll)
90617D	BLAST HOSE 42 X 9, SM-1	ID 42 mm - OD 60 mm (40 m roll)
99895D	BLAST HOSE 32 X 8, SM-1, 20 M, CQP-2, NHP-2	with nozzle holder and coupling
90297D	BLAST HOSE 32 X 8, SM-1, 40 M, CQP-2, NHP-2	with nozzle holder and coupling