



Blast Pot SCW-2048 (140l)

This high quality brand belongs to the product group “pressure blast systems”. Only the perfect configuration and match of all system components in a blast machine enable maximum blasting efficiency. Therefore Clemco offers an extensive and complete range of quality products.



Blast Pot SCW-2048 (140l)

Besides the different blast pot sizes, Clemco offers a large variety of different configuration possibilities for every blast machine. Our know-how that we have established over many years and our access to international resources enable us to find the perfect solution for your special needs. Our blast pots and assembly parts are designed according to the latest guidelines and meet highest standards. For Clemco it is absolutely self-evident that we only use best materials for our products to ensure a safe and economical operation.

| | |
|--------------------------------------------------------------------------------|---------------------------------|
| Total dimension: W x H x D * | 725 x 1340 x 700 mm |
| Diameter | 510 mm |
| Weight * | 130 kg |
| Tank capacity | 140 l |
| Abrasive media | suitable for every common media |
| Blasting pressure | 0 < > 12 bar |
| Operating temperature | 0°C < > 50°C |
| Features | depending on requirements |
| * +/- Values, may differ depending on configuration, arrangement and function. | |

Air volume in m³/min

| nozzle orifice | 3,5 bar | 4,2 bar | 4,9 bar | 5,6 bar | 6,3 bar | 7,0 bar | 8,6 bar | 10,3 bar |
|----------------|---------|---------|---------|---------|---------|---------|---------|----------|
| 5 mm 3/16" | 0,73 | 0,84 | 0,92 | 1,06 | 1,15 | 1,26 | 1,54 | 1,82 |
| 6,5 mm ¼" | 1,31 | 1,51 | 1,71 | 1,9 | 2,08 | 2,27 | 2,75 | 3,22 |
| 8 mm 5/16" | 2,16 | 2,5 | 2,83 | 3,16 | 3,53 | 3,84 | 4,71 | 5,57 |
| 9,5 mm 3/8" | 3,02 | 3,53 | 4 | 4,5 | 4,85 | 5,5 | 6,64 | 7,79 |
| 11 mm 7/16" | 4,12 | 4,76 | 5,44 | 6,09 | 6,73 | 7,11 | 8,8 | 10,48 |
| 12,5 mm ½" | 5,46 | 6,28 | 7,06 | 7,85 | 8,65 | 9,46 | 11,46 | 13,45 |

When selecting an air volume, please add 50% to the table values to allow loss for normal nozzle wear and friction.